

# Cables and connectors

|               |                                  |                         |
|---------------|----------------------------------|-------------------------|
| <b>Cables</b> | <b>Unprepared, cut to length</b> | <b>10 core + shield</b> |
|---------------|----------------------------------|-------------------------|



**TPE electronic trailing cable**

**4 x 2 x 0.25 mm<sup>2</sup> + 2 x 1 mm<sup>2</sup> + shield**



| Order details                                     | Order no.               |
|---|-------------------------|
| XXXX = cable length in meters (e. g. 10 m = 0010) | <b>8.0000.6400.XXXX</b> |

| Technical data                   |   |  |                               |
|----------------------------------|---|--|-------------------------------|
| <b>Cross section</b>             | 4 x 2 x 0.25 mm <sup>2</sup> + 2 x 1 mm <sup>2</sup> + shield   | <b>Features</b>  | <b>Cable construction</b><br> |
| <b>Working temperature range</b> | flexible installation: -40 °C ... +90 °C [-40 °F ... +194 °F]<br>fixed installation: -50 °C ... +90 °C [-58 °F ... +194 °F] | - halogen-free<br>- acid resistant<br>- oil resistant<br>- flexible at low temperatures<br>- low adhesion<br>- drag chain compatible |                               |
| <b>Bending radius cable min.</b> | flexible installation: 95 mm<br>fixed installation: 40 mm   |  |                               |
| <b>Cable sheath</b>              | cable diameter approx. 7.9 mm ±0.8 mm<br>material sheath: TPE   |  |                               |
|                                  |   |  |                               |