

## Preassembled cables

## M12 connection technology

## With connector, 4 pin



### Female connector with coupling nut, A coded, right-angle

### PUR cable, 4 x 0.34 mm<sup>2</sup> [AWG22]

flame retardant, seawater resistant, recyclable, PWIS free, acid/alkali/oil/ozon/UV resistant, halogen/silicone free, hydrolysis proof, drag chain-adapted, torsion resistant, welding sparks resistant

### Single-ended



## Order details


## Order no.

For supply voltage	Cable length	1 m [3.28']	<b>05.00.6061.6311.001M</b>
		2 m [6.56']	<b>05.00.6061.6311.002M</b>
		...	...
		xx m	<b>05.00.6061.6311.0xxM</b>
standard cable length (further on request)			xx = length in meters: 1, 2, 3, 5, 8, 10, 12, 15, 20, 25, 30

## Technical data

<b>Connector</b>	
material housing protection	metal / plastic IP67
<b>Wire cross sections</b>	
	4 x 0.34 mm <sup>2</sup> [AWG22]
<b>Working temperature range</b>	
flexible installation	-30 °C ... +90 °C [-22 °F ... +194 °F]
fixed installation	-40 °C ... +90 °C [-40 °F ... +194 °F]
<b>Bending radius cable min.</b>	
flexible installation	47.0 mm [1.85"]
fixed installation	23.5 mm [0.93"]
<b>Cable sheath</b>	
cable diameter approx.	4.7 mm ±0.2 mm
material sheath	PUR

### Dimensions in mm [inch]




## Connections

### Terminal assignment

Pin female contacts:	1	2	3	4
Core color:	BN	WH	BU	BK

### Plug-in face, A coded



## Suitable for our series

Encoders singleturn	Encoders multiturn	Draw-wire encoders	Linear measuring systems	Inclinometers
M3651A(R) / M3671A	M3661(R) / M3681	A41	Limes KIT TB1	IN81
M3658A / M3678A	M3668 / M3688	A50		
M5851A	M5861	B75		
M5858A	M5868	B80		
F5858 / F5878	F5868 / F5888	C60		
S5858 / S5878	S5868 / S5888	C100		
5858 / 5878	5868 / 5888	C105		
S3674	S3684	C120		
		D120		
		D125		
		D135		