

Safe speed monitors

Safety-M compact Basic module

Speed monitoring – SMC2.2

1 axis / 2 encoder systems



SIL3
Functional Safety
PLe

SMC2.2 is a compact safety module of the Safety-M family with integrated drive monitoring for one axis with 2 encoder systems. This standalone speed monitor (basic module) can be operated without additional safe PLC.

Safety-M compact is the optimal solution for integration in existing safety circuits or for retrofitting old machines. Two encoder solutions (HTL/proximity switch, TTL/RS422, SinCos) are supported for safe speed acquisition



TUV NORD

SinCos

RS422
TTL

Push-Pull
HTL

The integrated signal converter and splitter allows an easy connection of controllers, which can operate using the same encoder system. It offers in addition the possibility of issuing an analog rotational speed value, e.g. to replace tachometers or similar.

The device can be parameterized with a removable control and diagnostic display or with the PC software "OSxx". This way, setting and diagnostic can be performed conveniently at the office PC or totally and easily using the intuitive touchpad display in the field.

- Extensive library of pre-configured safe sensors and command devices. This allows easy parameterizing without programming.
- Complete range of speed-related safe drive monitoring functions equivalent to EN 61800-5-2 already integrated in firmware (e.g. SOS, SLS, SSM, STO).
- Different encoder interfaces for TTL/RS422, SinCos and HTL/Push-Pull/proximity switch, for a wide range of sensors that can be freely combined.
- Integrated signal splitter for SinCos signal forwarding (optional). No complex, interference-sensitive external wiring when the controller is to use the same signals.
- The signal converter can issue the encoder signal as SinCos, TTL/RS422 or as a 4 ... 20 mA analog value.
- Snap-on installation on 35 mm C profile rail.
- 4/2 safe input lines, 8/4 safe shut-off channels, 1 safe potential-free relay open contact.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts (EDM).
- LED on the front side indicates operating state.
- Removable control and diagnosis display (optional).
- Free "OSxx" parameterization software.

Order code

8 . SMC2 . 2 SA 241
a b c

a Encoder interface
2 = 2 x Sub-D SinCos

b Internal signal splitting
S = with

c Analog output
A = 4 ... 20 mA

1) Safety-M compact basic module.

2) Optional control and diagnosis display – to be ordered separately (see the accessories).

Safe speed monitors

Safety-M compact Basic module		Speed monitoring – SMC2.2	1 axis / 2 encoder systems
Accessories			Order no.
Control and diagnostic display, OLED touch screen			8.SMCB.100
“OSxx” parameterization software			download at www.kuebler.com/software
Shield terminal for encoder cable, C profile rail			Shield diameter 3.0 ... 12.0 mm 8.0000.4G06.0312
Connection technology			Order no.
Cordset, pre-assembled 2 m ¹⁾ for Sendix FS encoders	cable, single-ended / 1 x Sub-D, 9-pin, male connector		8.0000.6V00.0002.0087
	cable, single-ended / 1 x Sub-D, 9-pin, female connector		8.0000.6V00.0002.0086
	cable with 1 x M12 / 1 x Sub-D, 9-pin, female connector		8.0000.6V00.0002.0084

Further Kübler accessories can be found at: kuebler.com/accessories

Further Kübler cables and connectors can be found at: kuebler.com/connection-technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Technical data			
General data		Safety characteristics	
Digital input lines	4 / 2	Classification	PLe / SIL3
Digital output lines	8 / 4	System structure	2 channel (Cat. 3 / HFT = 1)
Safe relay outputs	1	PFH _d value	3.76 x 10 ⁻⁸ h ⁻¹
Type of connection	pluggable terminals	Mission time / Proof test interval	20 years
Max. terminal cross section	1.5 mm ² [AWG 15]	Reaction times	see operating instructions R60719
Drive monitoring - number of axis	1 axis	Relevant standards	EN ISO 13849-1:2008 EN 62061:2005 EN 61508:2011
Electrical characteristics		EMC	
Supply voltage	24 V DC / 2.5 A	Relevant standards	EN 61000-6-2:2005 / AC:2005 EN 61000-6-4:2007 / A1:2011 EN 61326-3-2:2008
Tolerance	±20 %		
Current consumption (no load)	max. 150 mA		
Power consumption	max. 45 W		
Fuse on supply voltage	max. 2.5 A, medium time-lag		
Rated encoder power supply data	approx. 2V below the supply voltage / max. 200 mA		
Environmental data		Mechanical characteristics	
Operating temperature	-20°C ... +55°C [-4°F ... +131°F]	Size w x h x d	50 x 100 x 165 mm [1.97 x 3.94 x 6.50"]
Storage temperature	-25°C ... +70°C [-13°F ... +158°F]	Weight	390 g [13.76 oz]
Protection acc. to EN 60529	IP20	Mounting	snap-on mounting on standard head rail
Climate class	3 acc. to DIN 50178 (non condensing)	Material	housing plastic
CE compliant acc. to	EMC guideline 2014/30/EU Machinery directive 2006/42/EC Low voltage guideline 2014/35/EU RoHS guideline 2011/65/EU	Shock resistance acc. to EN 60068-2-27	300 m/s ² , 11 ms 170 m/s ² , 6 ms
		Vibration resistance acc. to EN 60068-2-6	70 m/s ² , 10 ... 200 Hz
LED display			
ERROR (yellow)	steadily on flashing quickly flashing slowly	error peripheral alarm DIP 1 = OFF, factory setting DIP 3 = OFF, programming mode	
ON (green)	steadily on	power on	

¹⁾ Other lengths available

Safe speed monitors

Safety-M compact Basic module	Speed monitoring – SMC2.2	1 axis / 2 encoder systems
--	----------------------------------	-----------------------------------

SinCos interface (IN) X6, X7	
Type of connection	Sub-D, male connector, 9-pin
Signal	SinCos
Frequency	max. 500 kHz
Signal level	1 V _{pp} (±20 %)
Signal offset	2,5 V (±0,1 V)
Signal termination	120 Ω
Output voltage	2 V below the supply voltage
Output current	max. 200 mA

Incremental interface (IN) X8, X9	
Type of connection	pluggable screw terminals, 7-pin
Signal	RS422 / TTL
Frequency	max. 500 kHz
Signal termination	120 Ω, 220 pF

Digital inputs (IN) X10	
Type of connection	pluggable screw terminals, 5-pin
HTL signal	incremental interface, Proximity switches or digital inputs
Frequency	max. 250 kHz (incremental), max. 1 kHz (control signal)
Signal level	PNP (24 V DC / 15 mA)
Execution	complementary

Relay outputs (OUT) X1	
Type of connection	pluggable screw terminals, 2-pin
Wiring	two internally in line
Type	positively driven (NO)
Switching ability	5 ... 36 V DC
Switching capacity	5 ... 5000 mA

Digital switching outputs (OUT) X2	
Type of connection	pluggable screw terminals, 8-pin
Signal	HTL / push-pull
Rated data digital output	24 V DC / 30 mA

Incremental interface / RS422 (OUT) X4	
Type of connection	pluggable screw terminals, 7-pin
Signal	RS422 / TTL
Frequency	max. 500 kHz
Signal delay	SinCos <-> RS422: 600 ns RS422 <-> RS422: 600 ns HTL <-> RS422: 600 ns
Source	SinCos (X6, X7) incremental (X8, X9) HTL (X10)

Analog interface (OUT) X4	
Type of connection	pluggable screw terminals, 7-pin
Signal	analog
Resolution	14 bit
Accuracy	±0.1 %
Output	1 ms
Frequency	4 ... 20 mA
Load	max. 270 Ω



SinCos interface (OUT) X5	
Type of connection	Sub-D, female connector, 9-pin
Signal	SinCos
Signal level	1 V _{pp} (±20 %)
Signal offset	2,5 V (±0,1 V)
Frequency	max. 500 kHz
Signal delay	SinCos <-> SinCos 200 ns
Source	SinCos (X6)

USB interface X12	
Type	USB-B female connector
Standard	USB 1.0

Safe speed monitors

Safety-M compact Basic module	Speed monitoring – SMC2.2	1 axis / 2 encoder systems
--	----------------------------------	-----------------------------------

Terminal assignment



DIP switch S1

	off	on
1		
2		
3		

ON		Normal operation
OFF	1	Factory setting
	2	Self-test report
	3	Programming mode


X1 1 2 Relay OUT (NO) COM Relay	X2 1 2 3 4 5 6 7 8 Control OUT OUT 1 OUT 1 OUT 2 OUT 2 OUT 3 OUT 3 OUT 4 OUT 4	X3 1 2 Power 24 V IN GND 24 V IN	X4 1 2 3 4 5 6 7 Analog OUT RS422 OUT GND I OUT A GND A / A B / B	X8 1 2 3 4 5 6 7 RS422 IN 1 GND 24 V OUT A /A B /B GND	X9 1 2 3 4 5 6 7 RS422 IN 2 GND 24 V OUT A /A B /B GND	X10 1 2 3 4 5 Control IN GND A1 B1 A2 B2
---	--	--	---	--	--	--

If the analog output is not used, terminals X4.2 and X4.3 must be bridged.


Interface	Sub-D female connector										
Terminal X5	Signal: SinCos	A	\bar{B}	B	–	0 V	–	–	–	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

Interface	Sub-D male connector										
Terminal X6, X7	Signal: SinCos	A	\bar{B}	B	+V	0 V	–	–	–	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

+V: Power supply encoder +V DC
 0 V: Encoder power supply ground GND (0V)
 A, \bar{A} : Cosine signal / Incremental channel A
 B, \bar{B} : Sine signal / Incremental channel B
 PH \perp : Plug connector housing (Shield)



Sub-D female connector, 9-pin terminal X5



Sub-D male connector, 9-pin terminal X6, X7

Safe speed monitors

Safety-M compact Basic module


Speed monitoring – SMC2.2

1 axis / 2 encoder systems

Dimensions

Dimensions in mm [inch]

Basic module



Control and diagnostic display – 8.SMCB.100

(further information can be found in the section accessories)

